

Spark extinguishing system BM6

Product catalogue

A pair of hands is shown holding a small flame. A blue, ethereal shield or protective barrier is forming around the flame, symbolizing fire protection. The background is dark, and the hands are illuminated with a blue glow.


FIRE PROTECTION

MADE IN GERMANY

Spark detection units


SPARK DETECTION UNIT BM 6-2 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
4 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 400 x 600 x 200 mm
Protection Classification IP 55
Item number: 1021700




SPARK DETECTION UNIT BM 6-4 TOUCH

Microprocessor-controlled spark alarm unit equipped for 4 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
8 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 400 x 600 x 200 mm
Protection Classification IP 55
Item number: 1022700




SPARK DETECTION UNIT BM 6-16/2 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
4 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1023700




SPARK DETECTION UNIT BM 6-16/4 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
8 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1024700




SPARK DETECTION UNIT BM 6-16/6 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
12 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1025700




SPARK DETECTION UNIT BM 6-16/8 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
16 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1026700




SPARK DETECTION UNIT BM 6-16/10 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
20 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1027700




SPARK DETECTION UNIT BM 6-16/12 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
24 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1028700




SPARK DETECTION UNIT BM 6-16/14 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
28 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1029700



SPARK DETECTION UNIT BM 6-16/16 TOUCH

Microprocessor-controlled spark alarm unit equipped for 2 lines, expandable for up to 16 lines.
For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.
Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.
Option to implement PDF and video files.
Control panel for wall mounting.
Spark threshold programmable for activation of extinguishing system.
Log of 2500 events in the memory.
Built in emergency power supply for up to 4 hours operation.
32 free programmable relays per line.
32 languages installed, maybe switched at any time.
Optional: ProfiNet interface for data output.
Dimensions: 800 x 600 x 300 mm
Protection Classification IP 55
Item number: 1030700



SPARK DETECTION UNIT BM 6-36/0 TOUCH

Microprocessor-controlled spark alarm unit equipped for 36 lines (no lines included, has to be equipped with modules as required).

For connection of T&B spark detectors, smoke detectors, thermo detectors, flame detectors and manual buttons.

Intuitive touch display for visualization of alarms, number of sparks, extinguishing time, activated line.

Freestanding control panel.

Spark threshold programmable for activation of extinguishing system.

Log of 2500 events in the memory.

Built in emergency power supply for up to 4 hours operation.

72 free programmable relays.


32 languages installed, maybe switched at any time.

Optional interface for data output.

Dimension: 2200x800x600mm

Protection Classification IP 55

Item number: 1031700



EXTERNAL CONTROL AND DISPLAY PANEL BM6 TOUCH IN DESK CASE

The external control and display panel enables a spark detection unit to be operated from a remote location.

Dimensions: 403 x 290 x 150 mm

Protection class: IP 20

Item number: 1035003

