

Lumistar Timer


Externally located electronic timer, primarily for Lumistar luminaires and other electrical equipment

- Developed specifically for Lumistar luminaires
- Numerous time-setting options
- Timer can be retrofitted into existing systems
- Version with permanent operation switch is available

• **Time settings:** from 0.1 seconds to 20 hours

• **Protection class:** IP 65

• **Switching capacity, max.:**

Switching capacity Lumistar Timer	
	1 CO (SPDT) 16 A 250 V AC
	AC1 4000 VA
	AC15 (230 V AC) 750 VA
	Ⓜ (230 V AC) 0,55 kW
	DC1 (30/110/220)V (16/0.3/0.12)A

• **Cable entry gland:** 2 x M20 x 1.5 for cable 7-13 mm

• **Application temperature:** from -10 to +50°C

CE

3755.320



Lumistar Timer in synthetic housing



Lumistar Timer, stainless steel version

• **Bestellvorgaben:**

Lumistar Timer	Version	Product No.
Without permanent operation switch	Stainless steel housing	8670.042.00
Without permanent operation switch	Plastic housing	8670.051.00
With permanent operation switch	Stainless steel housing	8670.043.00

All dimensions in mm unless stated otherwise. Subject to change without prior notice. 11.15



CMC TECHNOLOGIES

PTY LIMITED ACN: 085 991 224, ABN: 47 085 991 224

Engineering & Industrial Instrumentation

Phone: +61 2 9669 4000
Fax: +61 2 9669 4111
Email: sales@cmctechnologies.com.au
Web Site: <http://www.cmctechnologies.net.au>

Unit 19, 77 Bourke Road,
Alexandria, NSW, 2015
AUSTRALIA

PAPENMEIER