

Mid-West[®] Instrument

“Piston Type” Model 121 Differential Pressure Switch & Transmitter

A low cost differential pressure indicating switch or transmitter for use in measuring the pressure drop across filters, strainers, separators, valves, pumps, chillers etc., and for local flow indication and control.

- ½ NPT conduit connection with heavy duty Switch or Transmitter cover and terminal strip
- Choice of 1 or 2 magnetically actuated hermetically sealed reed switches to provide high and low limit alarm or control or 4-20mA transmitter.
- Transmitter accuracy ± 2% full scale (from 20% to 100% of scale, ascending)
- Body materials: Aluminum or 316L Stainless Steel with 316 stainless steel internals.
- Weather-resistant construction standard.
- Working pressure up to 6,000 PSIG (700 bar)
- Over-range protection to maximum pressure.
- Shatter resistant acrylic lens.
- Variety of Dial type and Sizes: 2-1/2”, 3-1/2”, 4-1/2” & 6”
- Available DP Ranges: Inches H2O, PSID, bar, and Kpa
- Temperature Limits:
-40°F (-40°C) to +200°F (+93°C) (Switch Options)
-20° F to + 150° F (Transmitter Option)


**Transmitter now
CSA Listed for
Division 2 Hazardous
Location Service**



Model 121 0-75 PSID
2-1/2” Dial. Shown with
End Connections & Transmitter



Model 121 Switch
¼” FNPT back
connections



Model 121
0-50 PSID 4-1/2” Dial
& Transmitter



Model	Body Material	Gauge Accuracy	Min. ΔP Range	Max. ΔP Range	MWP PSIG (Bar)	Switch Options
121	Aluminum & 316L S.S.	±3/2/3%	0-5 PSID (0-0.35 bar)	0-100 PSID (0-7 bar)	ALM. = 3,000 (200 Bar) S.S. = 6,000 (400 Bar)	1 or 2 switches or 4-20mA Transmitter

Model 121 Indicating Switch(es) or 4-20mA Transmitter SPECIFICATIONS

TRANSMITTER

Features:

Microprocessor based, external zero interface:
8-28 Vdc loop powered, 2 wire interface

Electrical:

Accuracy ±2% (from 20% to 100% of scale, ascending)
Supply Voltage 8-28 Vdc
Output 4-20mA
Max Loop Resistance 1000 Ohms

Interface:

4 position terminal strip for 16-22 Awg wire
Pin 1 – return, Pin 2 = zero, Pin 3 = 8-28 Vdc, Pin 4-chassis
1/2” NPT conduit connection

SWITCHES

Features:

1 or 2 hermetically sealed reed switches

Electrical:


0-3W, 25 Amp
125 VAC (Adjustable 15-95% F.S.)
60W, 3.0 Amp
240 VAC (Adjustable 20-95%)

Interface:

7 position terminal strip for 16-22 Awg wire
1/2” NPT conduit connection

Environmental: Weatherproof
Rating: (NEMA 4X, IP65)

“Piston Type” Differential Pressure Switch & Transmitter Options Model 121



Open back view
Model 121 reed switch
with terminal strip



Model 121 Transmitter show
with NEMA 4X plastic cover



Open view Model 121 Transmitter
4-20 mA terminal strip
w/ 1/4" FNPT end connections

Piston-Type Differential Pressure Gauges are available with one or two hermetically sealed reed switches. The switches are adjustable within a defined percentage of the full scale range of the gauge and are available in SPDT and SPST, normally open or normally closed configurations for various load/power ratings. The switches can be set to activate or deactivate on rising or falling pressure. Switches are "CE" marked per the EU low voltage directive. Models 121 can be configured for use in Hazardous Locations.

Piston Type DP Gauge: $\pm 2\%$ Full Scale Accuracy. They are primarily designed for liquid applications. They exhibit a slight amount of bypass as the fluid crosses from the high to the low pressure port. Because gas molecules are smaller, the crossover is often deemed too great for the application. Due to precision sizing of piston and body bore, leakage across the piston will not exceed 32 SCFH air at 100 PSID at ambient conditions.

Available Electrical Configurations
One (1) Reed switch in NEMA 4X/IP65 Plastic enclosure with terminal strip (1/2" FNPT Conduit Connection)
Two (2) Reed switches in NEMA 4X/IP65 Plastic enclosure with terminal strip (1/2" FNPT Conduit Connection)
One (1) Switch in general purpose enclosure, Division 2 Hazardous Locations (1) (2)
Two (2) Switches in general purpose enclosure, Division 2 Hazardous Locations (1) (2)
4-20 mA Transmitter in NEMA 4X/IP65 Plastic enclosure with terminal strip (1/2" FNPT Conduit Connection) (4)
4-20 mA Transmitter in NEMA 4X/IP65 Plastic enclosure. Division 2 Hazardous Locations with terminal strip (1/2" FNPT Conduit Connection) (1) (2) (3)(4)
<i>(1) Complete assembly 3rd Party Certified Class I, Div.2, Groups A, B, C, & D; Class II, Div.2, Groups F and G.</i>
<i>(2) 5000 PSIG SWP for Stainless Steel: 3000 PSIG SWP for Aluminum</i>
<i>(3) Not available with 10,000 PSI SWP Division 2 Hazardous location switch</i>
<i>(4) Contact factory for flow applications with transmitter configuration</i>
Available Electrical Specifications (For Resistive Loads)
SPDT 3W, 0.25 Amp, 125 VAC/VDC (standard) (Switch adjustable range of 15-95%)
SPST 60W, 3.0 Amp, 240 VAC/VDC (Normally Open) (Switch adjustable range of 20-95%)
SPST 60W, 3.0 Amp, 240 VAC/VDC (Normally Closed) (Switch adjustable range of 20-95%)
SPST 60W, 3.0 Amp, 240 VAC/VDC (1) Normally Open, (1) Normally Closed (Switch adjustable range of 20-95%)
4-20 mA Transmitter (8-28 VDC Loop Power) ($\pm 2\%$ accuracy from 20% to 100% of scale. Ascending)

Proof Pressure: Two times rated working pressure at ambient temperature.

Temperature Limits:

Switch Options: -40°F to + 200°F / **Transmitter Options:** -20° F TO + 150° F

These limits are based on the entire instrument being saturated to these temperatures. System (process) temperatures may exceed these limitations with proper installation. Contact our customer service representative for details.

Standards: Model 121 Gauge either conforms to and/or is designed to the requirements of the following standards:

- | | |
|----------------------------|-----------------------------|
| ASME B1.20.1 | NACE MR0175 |
| ASME B40.100 | NEMA Std. No. 250 |
| CSA-C22.2 No. 14.25 and 30 | SAE J514 |
| EN-61010-1 | UL Std. No. 50.508 and 1203 |

Mid-West[®] Instrument

Standard Dial Ranges: Model 121

Range Type			
PSID	Kpa	Bar	Dual Scale
0-5 PSID	0-100 Kpa	0-1.0 Bar	0-5 PSID & 0-35 Kpa
0-10 PSID	0-160 Kpa	0-1.6 Bar	0-10 PSID & 0-0.7 Bar
0-15 PSID	0-250 kpa	0-2.0 Bar	0-15 PSID & 0-1 Bar
0-20 PSID	0-400 Kpa	0-2.5 Bar	0-25 PSID & 0-1.75 Bar
0-25 PSID	0-600 Kpa	0-4.0 Bar	0-30 PSID & 0-2.0 Bar
0-40 PSID	0-700 Kpa	0-6.0 Bar	0-30 PSID & 0-200 Kpa
0-30 PSID		0-7.0 Bar	0-40 PSID & 0-2.8 Bar
0-50 PSID			0-40 PSID & 0-2.75 Kpa
0-60 PSID			0-60 PSID & 0-4.0 Bar
0-75 PSID			0-100 PSID & 0-7.0 Bar
0-100 PSID			

The above mentioned ranges are some of the most popular requested today. Mid-West Instrument can provide special un-cataloged dial range requirements. As well as multiple scale dials, multiple color dials and special decals. Please consult factory for complete information.

Model	Min. ΔP Range	Max. ΔP Range
121	0-5 PSID (0-0.35 bar)	0-100 PSID (0-7 bar)

Proof Pressure: Two times rated working pressure at ambient temperature.

Temperature Limits:

Switch Options: -40°F to + 200°F

Transmitter Options: -20° F TO + 150° F

These limits are based on the entire instrument being saturated to these temperatures. System (process) temperatures may exceed these limitations with proper installation. Contact our customer service representative for details.

Standards: Model 121 Gauge either conforms to and/or is designed to the requirements of the following standards:

- | | |
|----------------------------|-----------------------------|
| ASME B1.20.1 | NACE MR0175 |
| ASME B40.100 | NEMA Std. No. 250 |
| CSA-C22.2 No. 14.25 and 30 | SAE J514 |
| EN-61010-1 | UL Std. No. 50,508 and 1203 |

Model 121 - continued



6	Additional Options
O	None
F	Carbon Steel 2" Pipe Mounting Kit
G	Stainless Steel 2" Pipe Mounting Kit
K	1/2" FNPT Stainless Steel Adapter
L	Liquid Fill (<i>Glycerin Fill Standard</i>) (2) (<i>Not available with shatterproof glass lens</i>)
M	Maximum Indicator Follower Pointer (<i>Not available w/3-1/2", 6" Dial or Liquid fill options</i>) (<i>Not available w/shatterproof glass lens</i>)
N	NACE
Q	CRN (Canadian Registration Number) (1)
S	Shatter Proof Glass Lens (<i>4-1/2" available with "G" option Aluminum Dial Case only</i>) (<i>Not available with liquid fill option</i>)
T	Oxygen Cleaning
U	Stainless Steel Tag with S.S. Wire
W	Wall Mount Kit (<i>Not available with back connections</i>)
Z	Special (Un-coded Options)
<i>(1) 5000 PSIG SWP for Stainless Steel</i>	
<i>(2) Silicone Fill available please contact factory</i>	
Note: Not All Options Available in Combination with other Options	
7	Electrical Configurations
A	One (1) Reed switch in NEMA 4X/IP65 Plastic enclosure with terminal strip (<i>1/2" FNPT Conduit Connection</i>)
B	Two (2) Reed switches in NEMA 4X/IP65 Plastic enclosure with terminal strip (<i>1/2" FNPT Conduit Connection</i>)
E	One (1) Switch in general purpose enclosure, Division 2 Hazardous Locations (1) (2)
F	Two (2) Switches in general purpose enclosure, Division 2 Hazardous Locations (1) (2)
T	4-20 mA Transmitter in NEMA 4X/IP65 Plastic enclosure with terminal strip (<i>1/2" FNPT Conduit Connection</i>) (3)
W	4-20 mA Transmitter in NEMA 4X/IP65 Plastic enclosure. Division 2 Hazardous Locations with terminal strip (<i>1/2" FNPT Conduit Connection</i>) (1) (2) (3)
Z	Special (Un-coded Options)
<i>(1) Complete assembly 3rd Party Certified Class I, Div.2, Groups A, B, C, & D; Class II, Div.2, Groups F and G.</i>	
<i>(2) 5000 PSIG SWP for Stainless Steel</i>	
<i>(3) Contact factory for flow applications with transmitter configuration</i>	
8	Electrical Specifications (For Resistive Loads)
A	SPDT 3W, 0.25 Amp, 125 VAC/VDC (<i>Switch adjustable range of 15-95%</i>)
E	SPST 60W, 3.0 Amp, 240 VAC/VDC (<i>Normally Open</i>) (<i>Switch adjustable range of 20-95%</i>)
F	SPST 60W, 3.0 Amp, 240 VAC/VDC (<i>Normally Closed</i>) (<i>Switch adjustable range of 20-95%</i>)
G	SPST 60W, 3.0 Amp, 240 VAC/VDC (1) <i>Normally Open</i> , (1) <i>Normally Closed</i> (<i>Switch adjustable range of 20-95%</i>)
T	4-20 mA Transmitter (8-28 VDC Loop Power) (<i>±2% accuracy from 20% to 100% of scale. Ascending</i>)
Z	Special (Un-coded Options)

MID-WEST INSTRUMENT has been serving a variety of industries for over 50 years. Over 700,000 piston type units have been produced bearing the Mid-West name or private branded for our OEM customers!

Mid-West understands that in today's demanding environment, flexibility, quick response time and the ability to ship product in 2 weeks or less is essential to our customers. Standard configurations can be customized and modified to suit our customer's needs for ease of installation or retrofit.



CMC TECHNOLOGIES

PTY LIMITED ACN: 085 991 224, ABN: 47 085 991 224

Engineering &
Industrial
Instrumentation

Phone: +61 2 9669 4000
Fax: +61 2 9669 4111
Email: sales@cmctechnologies.com.au
Web Site: <http://www.cmctechnologies.net.au>

Unit 19, 77 Bourke Road,
Alexandria, NSW, 2015
AUSTRALIA