

AIR PURGE FOR LIGHT CONDUCTOR

Adapter for applying compressed air before the Light conductor.
The air consumption of an air purge at 1 bar is approximately 70 l / min.
The air hose must have an external diameter of 6 mm.
The compressed air must have 3 to DIN ISO 8573-1 purity class.
Item number: 1590702



AIR PURGE FOR SPARK DETECTOR

Adapter for applying compressed air before the spark detector.
The air consumption of an air purge at 1 bar is approximately 70 l / min.
The air hose must have an external diameter of 6 mm.
The compressed air must have 3 to DIN ISO 8573-1 purity class.
Item number: 1590701



CONNECTION BOX KK3

For connection of 2 spark detectors, circuit board with 2 sockets.
Complete with cable glands.
(Also available as ATEX type).
Item number: 2010701



CONNECTION BOX KK3 ATEX

For connection of 2 spark detectors, circuit board with 2 sockets.
Complete with cable glands.
For mounting in Zone 21.
Item number: 2011702



CONNECTION BOX KK3 IECEx

For connection of 2 spark detectors, circuit board with 2 sockets.
Complete with cable glands.
For mounting in Zone 21.
Item number: 1550714



CONNECTION BOX KK3 LT

For connection of 2 spark detectors type FST-3 Lt, circuit board with 2 sockets.

Complete with cable glands.

Item number: 2010703



POLLUTION SENSOR VMS-1

Sensor with special quick-action fixture to control the degree of pollution at the spark detector.

With pre-assembled cable (2m).

Maximum ambient and product temperature may not exceed 60°C.

Not suitable for use in ATEX zones.

Item number: 1560701

